

ColorMeter



ColorMeter SE



ColorMeter Pro



ColorMeter MAX

ColorMeter SE/Pro/Max

Product Features

- Adopt D/8 (Diffused Illumination, 8 degree viewing) geometry and SCI to make measurement more accurate
- Adopt spectral sensor to provide reflectance data which make its performance much better than colorimeter
- Auto Calibration
- Data uploading background in the cloud can be edited for the second time
- Single machine or connected to the APP/PC can measure, and display the measurement results directly
- Find similar color, support customer to upload their own color information
- Android, ios, Windows (SE version not supported) operating systems



Technical Data

| Model | ColorMeter SE | ColorMeter Pro | ColorMeter Max |
|--------------------------|--|--|---|
| Geometry | D/8, Specular Component Included (SCI) | | |
| Color Spaces and Indices | CIE-Lab, ΔE^*ab , reflectance curve | Reflectance, CIE-Lab, CIE-LCh, Hunter Lab, CIE-Luv, XYZ, Yxy, RGB, Color Difference (ΔE^*ab , ΔE^*cmc , ΔE^*94 , ΔE^*00), Whiteness Index (ASTM E313-00, ASTM E313-73, CIE/ISO, AATCC, Hunter, Taube Berger Stensby), Yellowness Index, (ASTM D1925, ASTM E313-00, ASTM E313-73), Blackness Index (My,dM) Staining Fastness, Color Fastness, Tint (ASTM E313-00), Color Density CMYK(A,T,E,M), Metamerism Index Milm, Munsell, Opacity, Color Strength | |
| Light Source | LED (Full Wavelength Balanced LED Light Source) | | |
| Test Aperture | 8mm | | |
| Wavelength Interval | / | 10nm | |
| Wavelength Range | / | 400-700nm | |
| Repeatability | $\Delta E \leq 0.1$ (when a white tile is measured 30 times at 5-second intervals after calibration) | | $\Delta E \leq 0.05$ (when a white tile is measured 30 times at 5-second intervals after calibration) |
| Measurement Time | 1.5s | | 1s |
| Interface | USB (only for charging) | USB | |
| Illuminants | D65 | A, B, C, D50, D55, D65, D75, F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, F11, F12 CWF, U30, U35, DLF, NBF, TL83, TL84 | |
| Observer | 10° | 2° and 10° | |
| Screen | IPS Full Color Screen (screen resolution 135*240, 1.14 inches) | | |
| Battery | 4.2V/500mAh, Rechargeable, 5,000 continuous tests | 4.2V / 760mAh, Rechargeable, 10,000 continuous tests | |
| Calibration | Auto | | |
| Language | English and Chinese | | |
| Software Support | Android, IOS | Android, IOS, Windows | |
| Weight | About 90g | | |
| Instrument Size | Diameter 31mm, Height 102mm | | |